



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 4.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. CONTINUITY TEST WIRE END TO END: < 13mΩ.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. REF - OPERATING TEMPERATURE -20 TO 125°C.

3	9	TZZ10 BLACK	WIRE TZZ10 MIL-W-22759/16-10-0
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0366	HOUSING PTN24-PS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal Cable Harnesses
PTN24-PS-150-9-TZZ10-100-11

PART NUMBER **0367**

REVISION LEVEL **G**

PROJECTION