



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 1 MINUTE MIN.
2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. CONTINUITY CHECK 1 OHM MAX TO SOLDER CUP.
4. NO MOLD RELEASE ON SOLDER CUP SIDE.
5. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
6. WIRE COLOR ARRANGEMENT MAY VARY.
7. DIMENSIONS ARE INCHES [millimeters].

7	4	AMP #66569	CONTACT #18-22 SOLDER CUP GOLD PLATE
6	1	E26 WHITE	WIRE 26E MIL-W-16878/4 7/#34
5	1	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
4	1	E26 ORANGE	WIRE 26E MIL-W-16878/4 7/#34
3	1	E26 BLACK 7STRD	WIRE 26E MIL-W-16878/4 7/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	6-4RB-SS	HOUSING PT6-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION **PAVE-Seal Cable Harnesses**
PT6-SS-80-4-TE26-8-SC

PART NUMBER **0953**

REVISION LEVEL **E**

PROJECTION