



NOTES:

1. HE LEAK TEST @1 ATM. <10⁻⁷ CC/S.
2. TEST CONTINUITY: <.5W CONTACT TO WIRE END ON PCB.
<1W HOUSING TO PCB.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

14	A/R	PAVE-Seal 150	EPOXY BLACK
13	4.2"	E24 YELLOW	WIRE 24E MIL-W-16878/4 .010 7/#32
12	10.2"	E24 BROWN	WIRE 24E MIL-W-16878/4 .010 7/#32
11	10.1"	E24 RED	WIRE 24E MIL-W-16878/4 .010 7/#32
10	4.3"	E24 BLUE	WIRE 24E MIL-W-16878/4 .010 7/#32
9	4.2"	E24 GREEN	WIRE 24E MIL-W-16878/4 .010 7/#32
8	10.1"	E24 ORANGE	WIRE 24E MIL-W-16878/4 .010 7/#32
7	6	LOGAN#DD103CRL	CAPACITOR CERAMIC DISK
6	2	3M#3518	CONNECTOR PLUG POLARIZING KEY
5	1	3M#3408-6302	CONNECTOR 16 PIN
4	6	70001-30024	CONTACT SOC
3	1	70001-21730	PC BOARD ASSY
2	A/R	SN60	SOLDER SN60
1	1	0729	HOUSING TSQ
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION

0729-AL-150-6-TE24-PCB-10

PART NUMBER

0974

PROJECTION

