


9	1	M85049/52-1-10N	STRAIN RELIEF, SHELL SIZE 10
8	A/R	SUPER-O-LUBE	O-RING GREASE
7	1	MS3476-E10-6S	PLUG, STRT, 6 20AWG SOCKETS
6	1	MS3470-E10-6P	RECEPT. 6 20AWG PINS
5	1	PAVE #1180	VS12X-SS HOUSING
4	1	-116 VITON 75A	O-RING
3	A/R	PAVESEAL 200	EPOXY
2	6	E20, RED, 7 STRAND	WIRE, TYPE E TEFLON
1	1	8L5N-SS	VS12-SS NUT
ITEM	QTY	PART NUMBER	DESCRIPTION

NOTES:

1. LEAK TEST: 1029 PSI (70 BAR), THREAD SIDE, 1 HOUR HOLD, 5 CYCLES.
2. ELECTRICAL TEST: 630 VDC, 500 MEGOHMS MIN, WIRE TO WIRE & HOUSING.
3. REF-PART TO SHIP WITH NUT & MATING CONNECTOR W/STRAIN RELIEF.

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION
VS12X-SS-200-6-TE20-3470-18

PART NUMBER
1421

PROJECTION
