



NOTES:

1. HE LEAK TEST @1 ATM. 10×10^{-7} CC/S OR LESS.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM WITH MATING PLUGS.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS LARGER THAN $\phi.035$ [.89] ARE NOT ACCEPTABLE.
6. ITEMS 7, 8 & 9 ARE INCLUDED BUT NOT SHOWN.
7. ITEMS 7, 8 & 9 NOT INCLUDED WITH PART NUMBER 1482NP.
8. DIMENSIONS ARE INCHES [millimeters].

9	2	MS3057-16AN	STRAIN RELIEF 5015 SHELL 24
8	1	SC3106A24-28S	PLUG 24#16 SOC
7	1	SC3106A24-28P	PLUG 24#16 PIN
6	1	0185	NUT VS26-SS
5	1	-226 VITON	O-RING -226 VITON 75
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	SC3102A24-28S	RCPT 24#16 SOC BLACK RUBBER INSERT
2	1	SC3102A24-28P	RCPT 24#16 PINS BLACK RUBBER INSERT
1	1	1531	HOUSING VS26-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Mate I Connectors
VS26-SS-150-24-16-3102PS

PART NUMBER
1482

REVISION LEVEL
C
 PROJECTION