



NOTES:

1. MAXIMUM TORQUE TO TIGHTEN BOLT IN ROD IS 20 FT-LBS.
2. MAXIMUM PRESSURE IS FROM DIRECTION SHOWN.
3. NUTS ARE TIGHTENED WITH OPPOSING TORQUES.
4. INSTALLATION & LEAK TEST PORT CONFORM TO SAE J1926 BOSS DIMS.

6	2 PC	MCMAS ^T ER 9217A033	NUT, HEX JAM 1/2-13 BRASS
5	A/R	PARKER 884-4	O-LUBE, GREASE
4	1	-914 NEOPRENE70A	O-RING, -914 CHLOROPRENE 70A
3	A/R	PAVE-Seal 200HV	EPOXY, BLUE HIGH VOLT & TEMP
2	1 PC	PAVE 1558	COPPER ROD, É'5/8
1	1 PC	PAVE 1557	SO17L-PS HOUSING, BLACK
ITEM #	QUANTITY	SOURCE & PART #	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION

SO17LH-PS-200-1-63CU

PART NUMBER

1555

PROJECTION

