



NOTES:

1. ALL DIMENSIONS REFERENCE.
2. HE LEAK RATE <10-7 cc/s AE @1 ATM.
3. HIPOT TEST: 630VDC FOR .01s, 500 MEGOHM MIN.
4. ELECTRICAL CONTINUITY: <1 OHM PIN TO SOC.
5. SUPPLIED WITH MATING PLUGS SC3126F10-6P AND SC3126F10-6S, NOT SHOWN.

7	1	PAVE 0183	VS15-SS NUT
6	A/R	SUPER-O-LUBE	O-RING LUBRICANT
5	1	-215 VITON 75A	O-RING
4	A/R	PAVE-Seal 150	BLACK EPOXY
3	1	SC3112E10-6S	6 PIN 20GA QDB
2	1	SC3112E10-6P	6 PIN 20GA QDB 6 PIN (10-6) 6#
1	1	PAVE 0161	VS15L-SS HOUSING
ITEM	QTY	PART #	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION

VS15L-SS-150-6-20-3112SP

PART NUMBER

1564

PROJECTION

