



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HIPOT 1000 VDC 200 MΩ 0.01 SEC MINIMUM, ROD TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. DIMENSIONS ARE INCHES [millimeters].
6. REF-OPERATING TEMPERATURE RANGE:
 PAVE# 1573: -20°C TO 150°C
 PAVE# 1573-1: -20°C TO 200°C

1573-1	PT8-SS-200-1-.25CU-3-3	PAVE-Seal 200	EPOXY BLUE HIGH TEMP
1573	PT8-SS-150-1-.25CU-3-3	PAVE-Seal 150	EPOXY BLACK
PAVE#	PAVE DESCRIPTION	PART#	PART DESCRIPTION

5	A/R	SEE TABLE	EPOXY (SEE TABLE)
4	4	BRASS WASH 1/4"	WASHER 1/4" BRASS
3	4	BRASS NUTS 1/4"	NUT 1/4-20 UNF BRASS
2	1	0221-1	ROD COPPER .25
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PAVE technology co.

DESCRIPTION PAVE-Seal Cable Harnesses
 SEE TABLE

PART NUMBER **1573**

REVISION LEVEL **C**

PROJECTION