



NOTES:

1. LEAK TEST: 750 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HIPOT 1000 VDC 200 MΩ 0.01 SEC MINIMUM, ROD TO HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS LARGER THAN  $\phi.035$  [.89] ARE NOT ACCEPTABLE.
6. REF-OPERATING TEMPERATURE RANGE:  
 PAVE# 1573: -20°C TO 150°C  
 PAVE# 1573-1: -20°C TO 200°C
7. DIMENSIONS ARE INCHES [millimeters].
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

1573-1	PT8-SS-200-1-.25CU-3-3	PAVE-Seal 200	EPOXY BLUE HIGH TEMP
1573	PT8-SS-150-1-.25CU-3-3	PAVE-Seal 150	EPOXY BLACK
PAVE#	PAVE DESCRIPTION	PART#	PART DESCRIPTION

5	A/R	SEE TABLE	EPOXY (SEE TABLE)
4	4	BRASS WASH 1/4"	WASHER 1/4" BRASS
3	4	BRASS NUTS 1/4"	NUT 1/4-20 UNF BRASS
2	1	0221-1	ROD COPPER .25
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION	PAVE-Seal@ Cable Harnesses
SEE TABLE	
PART NUMBER	1573
REVISION LEVEL	D
PROJECTION	