



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MIN.
2. HYPOT 1000 VDC 500 MEGOHMS .01 SEC MINIMUM, ROD TO HOUSING.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

5	4	BRASS WASH 1/2"	WASHER 1/2" BRASS
4	4	BRASS NUTS 1/2"	NUT 1/2-20 UNF BRASS
3	1	1625	HOUSING PT16-SS
2	A/R	PAVESEAL 200HV	EPOXY BLUE
1	1	0169 .5CU	ROD .50" COPPER 200 AMP
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE STOCK NUMBER: STK 3



TITLE OR PAVE ORDER CODE PAVE-Seal® Cable Harnesses

PT16-SS-200HV-.5CU-2.4-3.0

PART NUMBER

1587

PROJECTION

