


PART#	DESCRIPTION	A	B	80 PSI TEST TIMES
1588	PT8-SS-200-9-TZ22-24-24	24 MINIMUM	24 MINIMUM	2 MINUTES MINIMUM
1588-1	PT8-SS-200-9-TZ22-12-59	12 ±0.5	59 ±0.5	3 MINUTES MINIMUM

NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES SEE CHART FOR TIMES. ALTERNATIVE TEST: 2000 PSI FOR 10 SECONDS.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN $\phi 0.035$ ARE ACCEPTABLE.
7. WIRE COLOR POSITIONS ARE APPROXIMATE AND VARIABLE.

11	1	TZ22 WHT 19	WIRE 22TZ MILW22759/44A .006 19/#34
10	1	TZ22 GREY 19	WIRE 22TZ MILW22759/44A .006 19/#34
9	1	TZ22 VIOLET 19	WIRE 22TZ MILW22759/44A .006 19/#34
8	1	TZ22 BLUE 19	WIRE 22TZ MILW22759/44A .006 19/#34
7	1	TZ22 GRN 19	WIRE 22TZ MILW22759/44A .006 19/#34
6	1	TZ22 YLW 19	WIRE 22TZ MILW22759/44A .006 19/#34
5	1	TZ22 ORG 19	WIRE 22TZ MILW22759/44A .006 19/#34
4	1	TZ22 RED 19	WIRE 22TZ MILW22759/44A .006 19/#34
3	1	TZ22 BROWN 19	WIRE 22TZ MILW22759/44A .006 19/#34
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal Cable Harnesses
PT8-SS-200-9-TZ22-SEE TABLE

PART NUMBER **1588**

REVISION LEVEL **G**

PROJECTION 