



NOTES:

1. ALL DIMENSIONS REFERENCE.
2. HE LEAK RATE <10-7 cc/s AE @1 ATM.
3. HIPOT TEST: 630VDC FOR .01s, 500 MEGOHM MIN.
4. ELECTRICAL CONTINUITY: <1 OHM PIN TO SOC.
5. SUPPLIED WITH MATING PLUGS SC3126F14-19P AND SC3126F14-19S, NOT SHOWN.

7	1	0115	INSERT VS18-SS
6	A/R	PAVE-Seal 150	EPOXY BLACK
5	1	PT-1014	NUT VS18-SS
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE-BASED
3	1	-219 VITON	O-RING -219 VITON 75A
2	1	SC3112E14-19S	RCPT 19#20 SOC
1	1	SC3112E14-19P	RCPT 19#20 PIN
ITEM	QTY	ITEM NUMBER	ITEM DESCRIPTION

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.paveotechnologyco.com

DESCRIPTION
VS18-E-150-19-20-3112PS

PART NUMBER **1651** PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS