


NOTES:

1. WIRES MUST BE DIFFERENT COLORS, TO BE DETERMINED BY PAVE STOCK.
2. LEAK TEST: 200 PSI N2, 30 SEC MIN., NO BUBBLES.
3. HIPOT TEST: 630VDC, 500MEGOHMS, .01SEC MIN., WIRE TO WIRE TO HOUSING.


5	A/R	PAVE-Seal 80	EPOXY, BLACK
4	13"	PC24	WIRE, 24 AWG, SEE NOTE 1
3	13"	PC24	WIRE, 24 AWG, SEE NOTE 1
2	13"	PC24	WIRE, 24 AWG, SEE NOTE 1
1	1	PARKER 2-1 RB-B	HOUSING, PT2-B
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION
PT2-B-80-3-PC24-6-6

PART NUMBER 1675	PROJECTION 
----------------------------	---