



PART #	A	B	C
1773	48	48	100.2
1773-1	48	144	196.2

- NOTES:
- HE LEAK TEST @1 ATM. <math><10^{-8}</math> CC/S.
  - HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
  - FINISH FOR %C3.1 MINIMUM SPOTFACE.
  - ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
  - ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
  - ASSEMBLY WITH LONGER LEADS IS 1773-1  
DESCRIPTON: VS32-SS-150-80P-48-144

6	1	0102	NUT VS32-SS
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
4	1	-231 VITON	O-RING -231 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	80@C"	KT20	WIRE T/C 20KT TYPE K
1	1	0101	HOUSING VS32-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**VS32-SS-150-80P-KT20-48-48**

PART NUMBER **1773** PROJECTION