


## BULKHEAD LAYOUT



### NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2 MINUTES MIN.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

7	A/R	PAVESEAL 80	EPOXY BLACK
6	1	0894	NUT VS8-SS
5	A/R	PARKER-O-LUBE	LUBRICANT O-RING BARIUM BASED
4	1	-112 VITON	O-RING -112 VITON 75A
3	1	0892	HOUSING VS8-SS
2	1@725	EE18 GRN	WIRE 18EE MIL-W-16878/5 GREEN
1	1@725	EE18 BLK	WIRE 18EE MIL-W-16878/5 BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-13  
 X DECIMAL +/- 2.5 XX DECIMAL +/- .50 XXX DECIMAL +/- 100  
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS



DESCRIPTION PAVE-Seal/E Cable Harnesses  
**VS8-SS-80-2-TEE18-30-40CM**

PART NUMBER  
**1805**

PROJECTION

