



INSTALLATION BORE-  
REFERENCE ONLY

**NOTES:**

1. LEAK TEST: 300 PSI N2, NO BUBBLES.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, CONTACT TO CONTACT.

4	2	605031	CONTACT #24 MONEL VICKERS
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM
2	1	-010 BUNA	O-RING -010 BUNA 75
1	1	0168	HOUSING SP6-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

TITLE OR PAVE ORDER CODE

SP6-E-200-2-24-T

PART NUMBER

1847

PROJECTION

