


NOTES:

1. LEAK TEST: 25 BAR (368 PSI), NO BUBBLES 1 MINUTE MINIMUM.
2. HYPOT 630 VDC 500 MΩ .01 SEC MINIMUM, WIRE TO WIRE.
3. THERMAL CYCLE: -40° TO 125°, 3 CYCLES WITH 1 HOUR HOLD AT TEMP.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

3	1	PAVE-Seal 150	HOUSING SP5P-E
2	2.20FT	XLP22 UL WHT	WIRE 22XLP UL3265 IRR POLY .052 OD 19/#34
1	2.20FT	XLP22 UL RED	WIRE 22XLP UL3265 IRR POLY .052 OD 19/#34
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN MM
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-13
 X.X DECIMAL +/-2.5 X.XX DECIMAL +/-0.50 X.XXX DECIMAL +/-0.100
 ANGLES +/- 1 DEG SURFACE FINISH 3.2 micrometers RMS



PAVE technology co.

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION *PAVE-Seal@ Cable Harnesses*
SP5P-E-150-2-XLP22-.3m-.3m

PART NUMBER 1877	REVISION LEVEL A
PROJECTION 