



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 5 SECONDS MINIMUM W/ -013 VITON O-RING & 1119 LTP.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, CUP TO CUP.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

2	12	1986	CONTACT #20 SOLDER CUP BARE
1	1	PAVE-Seal 80	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

---

TITLE OR PAVE ORDER CODE **PAVE-Mate® I Connectors**  
**SPF9-E-80-6-20-SC-SC**

---

PART NUMBER <span style="font-size: large; font-weight: bold;">1990</span>	PROJECTION 
---	----------------