



- NOTES:**
1. REF - SHOULD PASS HE LEAK TEST @1 ATM. <10⁻⁷ CC/S.
 2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 3. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.
 4. PACKAGE IN THE BOX THE FIBER IS SUPPLIED IN.

3	A/R	EN-1556 BLACK	URETHANE BLACK
2	1	8FIBERARRAY3MLG	FIBER OPTIC ARRAY OF 8 TERMINATED
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Flex® Cable Harnesses
TBS-E-150-8-FO-42-2.74

PART NUMBER	PROJECTION
2000	