



**NOTES:**

1. LEAK TEST: 500 PSI, NO BUBBLES 4 MINUTES MIN.
2. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.
5. 0189 HOUSING MODIFIED PER PAVE 2042.

6	1	0199	NUT VS22-SS
5	A/R	PAVESEAL 200	EPOXY BLACK
4	A/R	SUPER-O-LUBE	LUBRICANT O-RING SILICONE BASED
3	1	-224 VITON	O-RING -224 VITON 75A
2	1	0189 <small>SEE NOTE 5</small>	HOUSING VS22-SS
1	20P@87"	RXT20	CABLE T/C 20 TYPE RX TEFLON
ITEM	QTY.	ITEM NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
**VS22-SS-200-20P-RXT20-24-60**

PART NUMBER  
**2032**

PROJECTION

