



ITEM ID	A	B	DESCRIPTION
2035	180	36	VS8-SS-150-1P-SX20-180-36
2035-1	12	100	VS8-SS-150-1P-SX20-12-100

- NOTES:
1. LEAK TEST: 80 PSI, NO BUBBLES 10 MINUTES MINIMUM.
  2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE, DRAIN WIRE, & HOUSING.
  3. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
  4. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

5	1	VS8-SS NUT	NUT VS8-SS PARKER 5-WLZ-SS
4	1	-112 VITON	O-RING -112 VITON 75
3	1	SX20 CABLE	CABLE T/C 20 ANSI SX TWSH
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0892	HOUSING VS8-SS 316SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
**PAVE technology co.**  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal Cable Harnesses**  
**SEE TABLE**

PART NUMBER **2035**

REVISION LEVEL **B**

PROJECTION