



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 4 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE, SHIELD & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	A/R	PAVE-Seal 200	EPOXY BLACK
2	5@98"	KF22	CABLE T/C TYPE K 22AWG
1	1	2148	HOUSING PT20-SS 316SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.

DESCRIPTION **PAVE-Seal® Cable Harnesses**
PT20-SS-200-5P-KF22-48-48

PART NUMBER
2234

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

PROJECTION