



| PART # | (X) | Y | Z | NETWOCO # | W |
|--------|-----|------|------|-----------|----|
| 2253 | 7 | 10.3 | 17.3 | 900729 | 50 |
| 2253-1 | 12 | 17.5 | 29.5 | 90072902 | 75 |

NOTES:
 1. HE LEAK TEST 10% OF PARTS @1 ATM. <10⁻⁶ CC/S.
 2. CHECK OPTICAL CONTINUITY.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. ITEMS 3 THRU 5 CUSTOMER SUPPLIED.
 5. HANDLE ITEMS 3 THRU 5 CAREFULLY-1" DIA MIN COIL GLASS FIBER BREAKS WHEN BENT SHARPLY.
 6. REAPPLY PLASTIC CAPS TO TERMINALS DURING HANDLING.

| 8 | 1 | 0894 | NUT VS8-SS |
|------|----------------|------------------|---------------------------------|
| 7 | A/R | SUPER O-LUBE | LUBRICANT O-RING SILICONE BASED |
| 6 | 1 | -112 BUNA | O-RING -112 BUNA 75 |
| 5 | Z SEE TABLE | 7120555-40-2050R | SMFO FC/UPC to LC/UPC WCM RED |
| 4 | Z SEE TABLE | 7120555-40-2050W | SMFO FC/UPC to LC/UPC WCM WHITE |
| 3 | Z SEE TABLE | 7120555-40-2050B | SMFO FC/UPC to LC/UPC WCM BLUE |
| 2 | A/R | PAVE-Seal | EPOXY BLACK |
| 1 | 1 | 2265 | HOUSING VS8-AL |
| ITEM | QTY | PART# | DESCRIPTION |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION [PAVE-Opti SealFromans.shx; Cable Harnesses](#)
VS8-AL-150-3-FOSMF28-7-10

PART NUMBER **2253** PROJECTION