



NOTES:
 1. HELIUM LEAK TEST @1 ATM. 10^{-8} CC/S.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL HOUSING DIMENSIONS FOR REFERENCE ONLY.
 5. ITEM 5 SHIELDING NEED NOT BE CARRIED THROUGH CONTINUITY THROUGH HOUSING.

7	A/R	PAVE-SEAL 80	EPOXY BLACK
6	2	KT27	CABLE T/C TYPE K 27 AWG TEFLON
5	1	CABLE 2/C #16	CABLE 2/C #E16
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILCONE-BASED
3	1	-116 VITON	O-RING -116 VITON 75
2	1	8L5N-SS	NUT VS12-SS
1	1	1180	HOUSING VS12L-SS

ITEM QTY PART # DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE Technology Co.
 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses
 VS12L-SS-80-1TSP/2P-TE16/KT27-6-6

PART NUMBER **2381** PROJECTION