


2408-3	PC2 GRN
2408-2	PC2 BLUE
2408-1	PC2 BLK
2408	PC2 RED
PART NUMBER	ITEM 3 PART#

NOTES:

1. LEAK TEST: 170 PSI, NO BUBBLES 7.5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO HOUSING.
3. CONTINUITY TEST WIRE END TO END: <6mΩ.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	1	SEE TABLE	WIRE 2PC UL1283 19/.0591 .419
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	8-4RB-SS	HOUSING PT8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal Cable Harnesses**
PT8-SS-150-1-PC2-120-240

PART NUMBER **2408**

REVISION LEVEL **A**

PROJECTION 