



NOTES:

1. LEAK TEST: QUALIFICATION ONLY: HE LEAK TEST @ 80 PSI. 10^{-7} CC/S (80PSI ON CONNECTOR SIDE). 100%: HE LEAK TEST @ 1 ATM 10^{-7} CC/SEC.
2. HYPOT 630 VDC 500 MEGAOhms 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING W/ MATING CONNECTOR.
3. CONTINUITY TEST: 0.5 Ohms OUTER SHIELD WIRE TO CONNECTOR, INSIDE SHIELD TO ITEM 3 & CONDUCTOR TO ITEM 2.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

8	A/R	SUPER O-LUBE	LUBRICANT SILICONE BASED
7	1	RR N5001-12	RETAINING RING EXTERNAL .125
6	1	E26 BLACK 7STRD	WIRE 26E MIL-W-16878/4 7/#34
5	1	-005 VITON	O-RING -005 VITON 75
4	A/R	PAVE-Seal 150	EPOXY BLACK
3	1	E20 BLUE	WIRE 20E MIL-W-16878 .010 7/28
2	1	E20 ORG	WIRE 20E MIL-W-16878 .010 7/28
1	1	015100-3000	SABRITEC NDL-T
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

		2751 Thunderhawk Court Dayton, OH 45414-3445 U.S.A. tel (937) 890-1100 fax (937) 8905165 www.pavetechnologyco.com	
		DESCRIPTION SP4-E-150-2/1-TE20/TE26-TRIAXIAL-12	
PART NUMBER 2669		REVISION LEVEL - PROJECTION	