



**NOTES:**

1. LEAK TEST <math>10^{-6}</math> CC/S @ 900 PSI HELIUM.
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE

A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.

5	A/R	PAVE-Seal 150	EPOXY BLACK
4	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM BASED
3	1	-112 VITON	O-RING -112 VITON 75
2	5	KT24	CABLE T/C TYPE K 24AWG TEFLON
1	1	0892 VS8-SS	HOUSING VS8-SS 316SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
**VS8-SS-150-5P-KT24-10-10**

PART NUMBER **2716** REVISION LEVEL -  
 PROJECTION