



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-7} CC/SEC OR LESS.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. ALL PARTS MUST PASS ALL TESTS.
4. FIBER POSITIONING IS APPROXIMATE & VARIABLE.
5. NO VOIDS LARGER THAN $\phi 0.035$ ARE ACCEPTABLE IN THE EPOXY.

6	1	0894	NUT VS8-SS
5	1	E38ULUS1.2FISCL	FIBER SINGLE MODE 9/125 SMF28E CLEAR BARE FIBER
4	1	E38ULUS1.2FISBL	FIBER SINGLE MODE 9/125 SMF28E BLUE BARE FIBER
3	1	-112 BUNA	O-RING -112 BUNA 75
2	1	0892	HOUSING VS8-SS
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
VS8-SS-150-2-SMF28E-36LC-12ST

PART NUMBER
3123

REVISION LEVEL
C

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS