



NOTES:

1. HE LEAK TEST @ 1 ATM 10×10^{-8} CC/SEC OR LESS.
2. HYPOT 500 VDC 200 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. CONTINUITY TEST 0.5 OHMS MAXIMUM MATING CONNECTOR TO MATING CONNECTOR.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN $\phi 0.035$ ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. REF-OPERATING TEMPERATURE -20°C TO 150°C .
8. DIMENSIONS ARE INCHES [MILLIMETERS].

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

6	1	-026 VITON 75	O-RING -026 VITON 75
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	4	JACKPOST	"P" STYLE 2-56 UNC
3	1	3174	HOUSING SP33/14-AL 6061 ELECTROLESS NICKEL PLATED
2	1	M8351303-G05N	CONNECTOR 51PIN MIL-C-83513
1	1	M83513/02-GN	CONNECTOR 51SOC MIL-C-83513
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 SP33/14-AL-150-51-25-M83513

PART NUMBER
3142

MATERIAL NOTED

REVISION LEVEL
 F

PROJECTION