


NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN $\phi 0.035$ ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20°C TO 150°C .

3	24	KAPTON K22	WIRE 22 KAPTON M81381/12-22-N
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3269	HOUSING PTNF20-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 .X DECIMAL ± 0.1 .XX DECIMAL ± 0.02 .XXX DECIMAL ± 0.005
 ANGLES ± 1 DEG SURFACE FINISH 128 microinch RMS


 2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION **PAVE-Seal Cable Harnesses**
PTNF20-SS-150-24-K22-60-60

PART NUMBER	REVISION LEVEL
3262	-
PROJECTION	