



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 5 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
6. NO VOIDS LARGER THAN  $\phi 0.035$  ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE  $-20^{\circ}\text{C}$  TO  $150^{\circ}\text{C}$ .

3	24	KAPTON K22	WIRE 22 KAPTON M81381/12-22-N
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3269	HOUSING PTNF20-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
 .X DECIMAL  $\pm 0.1$  .XX DECIMAL  $\pm 0.02$  .XXX DECIMAL  $\pm 0.005$   
 ANGLES  $\pm 1$  DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

**PAVE technology co.**

DESCRIPTION PAVE-Seal Cable Harnesses  
**PTNF20-SS-150-24-K22-60-60**

PART NUMBER  
**3262**

REVISION LEVEL -  
 PROJECTION