



**NOTES:**

1. HE LEAK TEST VACUUM 10X10<sup>-7</sup> CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND RECEPTACLE FLANGES.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø.035 [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. CONTINUITY TEST <.5 Ohms PINS TO SOCKETS.
7. REF-OPERATING TEMPERATURE -20 °C TO 105 °C.
8. DIMENSIONS ARE INCHES [millimeters].

7	1	3466	PLATE TOP SS
6	1	-029 VITON	O-RING -029 VITON 75
5	4	JACKPOST 4-40	"P" STYLE 4-40 UNC
4	2	YARDLEY#440A5-8	THREADED INSERT SS
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	4008-15	RCPT D-SUB 15 SOCKET
1	1	4007-15	PLUG D-SUB 15 PIN
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION		SP37/13-E-150-15-20-DSUB-DSUB	
PART NUMBER	MATERIAL	NOTED	
<b>3362</b>	REVISION LEVEL	A	PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS