



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 2.5 MINUTES MINIMUM, PRESSURE ON VACUUM SIDE OF HOUSING.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. VOIDS SMALLER THAN  $\phi$  .035 [.89] ARE ACCEPTABLE.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON EACH SIDE OF HOUSING.
8. REF-OPERATING TEMPERATURE -20°C TO 150°C.
9. DIMENSIONS ARE INCHES [millimeters].

4	8	BRADY MARKERS	BRADY MARKERS 1-4
3	4	TT24	CABLE T/C TYPE T#24 TEFLON
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0346	HOUSING PT8-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION PT8-SS-150-4P-TT24-36-18	
PART NUMBER <b>3379</b>	MATERIAL NOTED REVISION LEVEL B
PROJECTION	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5  
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005  
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS