



NOTES:

1. MATERIAL TO BE IDENTIFIED (ENGRAVED) PER CUSTOMER SPEC.
2. LEAK TESTING: NO VISIBLE BUBBLES AT 80 PSI DRY NITROGEN GAS ON THREAD SIDE.
3. OPTIONAL HELIUM LEAK TEST LESS THAN  $1 \times 10^{-6}$  CC/SEC
4. ELECTRICAL HYPOT TEST 630 VDC MORE THAN 500 MEGOHM
5. PACKAGE PER CUSTOMER SPECS.
6. EPOXY DISPENSING KITS PT-1064 AVAILABLE UPON REQUEST.

-6

4	1	PT-1054	SOCKET PLUG ASY 19 #22AWG
3	1	PT-1053	PIN PLUG ASY 19
2	1	PT-1047	PUSHTHRU ASY 19 #22AWG
1	1	PT-1007	HOUSING ASSY
ITEM #	QTY	PART #	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 1.28 microinch RMS

**PAVE technology co.**

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 937.890.1100  
 fax 937.890.5145  
 www.pavetechnologyco.com

DESCRIPTION:  
**PUSHTHRU & PLUG ASY 19 PIN**

PART NUMBER: **PT-1046**

PROJECTION: