



**NOTES:**

1. LEAK TEST: 1200 PSI, NO BUBBLES 30 SECONDS MINIMUM. QUALIFICATION ONLY: 3500 PSI
2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

11	1@25	EE26 UL1180 VIO	WIRE 26EE UL1180 7/#34
10	1@25	EE26 UL1180 RED	WIRE 26EE UL1180 7/#34
9	1@25	EE26 UL1180 ORG	WIRE 26EE UL1180 7/#34
8	1@25	EE26 UL1180 GRY	WIRE 26EE UL1180 7/#34
7	1@25	EE26 UL1180 GRN	WIRE 26EE UL1180 7/#34
6	1@25	EE26 UL1180 BRN	WIRE 26EE UL1180 7/#34
5	1@25	EE26 UL1180 BLU	WIRE 26EE UL1180 7/#34
4	1@25	EE26 UL1180 YEL	WIRE 26EE UL1180 7/#34
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	2	-012 VITON LT	O-RING -012 LOW-TEMP VITON 75
1	1	1226 SP8M	HOUSING SP8M-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses  
 SP8M-E-200-8-TEE26-2-12

PART NUMBER  
**2333**

