



- NOTES:
 1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

16	1FT	E28 WHT/ORG	WIRE 28E MIL-W-16878/4 .010 7/#36
15	1FT	E28 WHT/BLU	WIRE 28E MIL-W-16878/4 .010 7/#36
14	1FT	E28 WHT/GRN	WIRE 28E MIL-W-16878/4 .010 7/#36
13	1FT	E28 YELLOW	WIRE 28E MIL-W-16878/4 .010 7/#36
12	1FT	E28 WHITE	WIRE 28E MIL-W-16878/4 .010 7/#36
11	1FT	E28 VIOLET	WIRE 28E MIL-W-16878/4 .010 7/#36
10	1FT	E28 RED	WIRE 28E MIL-W-16878/4 .010 7/#36
9	1FT	E28 ORANGE	WIRE 28E MIL-W-16878/4 .010 7/#36
8	1FT	E28 GREEN	WIRE 28E MIL-W-16878/4 .010 7/#36
7	1FT	E28 GRAY	WIRE 28E MIL-W-16878/4 .010 7/#36
6	1FT	E28 BROWN	WIRE 28E MIL-W-16878/4 .010 7/#36
5	1FT	E28 BLUE	WIRE 28E MIL-W-16878/4 .010 7/#36
4	1FT	E28 BLACK	WIRE 28E MIL-W-16878/4 .010 7/#36
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	1	-012 VITON	O-RING -012 VITON 75
1	1	1226-S	HOUSING SP8S-E
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/- 0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses

SP8S-E-150-13-TE28-5-5

PART NUMBER

2394

PROJECTION

