



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN $\phi .035$ [.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. REF-OPERATING TEMPERATURE -40°C TO 125°C .
8. DIMENSIONS ARE INCHES [millimeters].

8	1	FIT-321V-3/4	TUBING SHRINK 3/4" IRR POLYOLEFIN BLACK
7	2	M23053/6-105-0	TUBING SHRINK HEAT POLYOLEFIN BLACK
6	1	PAPVF24 WHITE	WIRE #24POLYALKENE-PVF M81044/12
5	2	PAPVF24 RED	WIRE #24POLYALKENE-PVF M81044/12
4	1	PAPVF24 BLUE	WIRE #24POLYALKENE-PVF M81044/12
3	2	PAPVF24 BLK	WIRE #24POLYALKENE-PVF M81044/12
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	3433	HOUSING FL10-AL ANODIZED CLASS II
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION FL10-AL-150-6/4-PAPVF24-6-4	
PART NUMBER 3380	MATERIAL NOTED
REVISION LEVEL A	PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS