



NOTES:

1. HE LEAK TEST VACUUM 10×10^{-7} CC/SEC OR LESS.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING WITH MATING CONNECTORS.
3. CONTINUITY TEST ALL CONDUCTORS : $<.5$ OHM W/ MATING CONNECTORS.
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. VOIDS LARGER THAN $\text{Ø}.035$ [.89] ARE NOT ACCEPTABLE.
7. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
8. REF-OPERATING TEMPERATURE -20°C TO 50°C .
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

5	A/R	PAVE-Seal 150	EPOXY BLACK
4	1	0183	NUT VS15-SS
3	1	-215 VITON	O-RING -215 VITON 75
2	3	70615	CABLES USB TYPE A MALE TO FEMALE 1FT
1	1	0161	HOUSING VS15L-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION	
VS15L-SS-150-3-USBA-4M-4F	
PART NUMBER	MATERIAL NOTED
3538	
REVISION LEVEL	PROJECTION
A	

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS