



NOTES:

1. LEAK TEST: 2000 PSI, NO BUBBLES 10 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS 0.01 SEC MINIMUM, WIRE TO WIRE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. WIRES ARE NOT REQUIRED TO BEND SHARPLY AT EPOXY SEAL SURFACE.
5. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN Ø0.035 [0.89] ARE ACCEPTABLE ON ALL OTHER SURFACES.
6. WIRE POSITIONS ARE APPROXIMATE & VARIABLE.
7. DIMENSION IS OVER-ALL-LENGTH EXCLUDING OVERFILL ON ATMOSPHERE SIDE OF HOUSING.
8. (PARTS ARE DEFLASHED ON PARTING LINE +0.005 [0.13] MAXIMUM.)
9. DIMENSIONS ARE INCHES [MILLIMETERS].
10. REF-OPERATING TEMPERATURE RANGE -20 TO 125C.

5	1	PC20 UL1569 BLK	WIRE 20PVC UL1569 .016 7/#28
4	1	PC20 UL1569 RED	WIRE 20PVC UL1569 .016 7/#28
3	A/R	PARKER O-LUBE	LUBRICANT O-RING BARIUM-BASED
2	2	-012 VITON	O-RING -012 VITON 75
1	A/R	PAVE-Seal 150	EPOXY BLACK
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
SP8L-E-150-2-PC20-6-6

PART NUMBER
3660

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS