



NOTES:

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MΩ MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. VOIDS SMALLER THAN $\phi .035$ [.89] ARE ACCEPTABLE.
6. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
7. DIMENSIONS ARE INCHES [millimeters].
8. OPERATING TEMPERATURE RANGE -20°C TO 85°C.
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

3	9	THHN 18 BLACK	WIRE 18THHN BLACK
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0073	HOUSING PTN12-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.

2751 Thunderhawk Court
Dayton, OH 45414-3445
U.S.A.
tel (937) 890-1100
fax (937) 8905165
www.pavetechnologyco.com

DESCRIPTION
PTN12-SS-150-9-THHN18-36-36

PART NUMBER 4338	MATERIAL NOTED
REVISION LEVEL A	PROJECTION ☉ ◁

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ±0.5
X.X DECIMAL ±0.1 X.XX DECIMAL ±0.02 X.XXX DECIMAL ±0.005
ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS