



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-5} CC/S.
2. HYPOT 630 VDC 500 M.01 SEC MINIMUM, WIRE TO WIRE, SHIELDS & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL SPECIFICATIONS AND TESTS SUPERSEDE PAVE CATALOG SPECIFICATIONS.

6	1	0199	NUT VS22-SS
5	A/R	PAVE-Seal 150	EPOXY BLACK
4	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE
3	1	-224 VITON	O-RING -224 VITON 75
2	1	0189	HOUSING VS22-SS
1	11	RG178	WIRE COAX RG178

ITEM	QTY	PART#	DESCRIPTION
------	-----	-------	-------------

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

PAVE technology co.

2751 Thunderhawk Court
 Dayton, Ohio 45414-3445
 U.S.A.
 (937)890-1100
 fax (937)890-5165
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses

VS22-SS-150-11-RG178-60-60

PART NUMBER	PROJECTION
1389	