



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S AIR EQUIVALENT. (AIR EQUIVALENT LEAK RATE/2.73 = ACTUAL He LEAK RATE)
2. LEAK TEST: 100 PSI, THREAD SIDE, NO VISIBLE LEAKS, QUALIFICATION ON FIRST ARTICLE(S) ONLY.
3. HYPOT 630 VDC 500 MEGOHMS .01 SEC MINIMUM, TAB TO TAB & HOUSING.
4. ALL TESTS ARE DONE AT ROOM TEMPERATURE.
5. THESE SPECIFICATIONS SUPERSEDE PAVE CATALOG.

5	A/R	PARKER SUPER-O-LUBE	VACUUM GREASE SILICONE BASED
4	A/R	PAVESEAL 200	EPOXY BLACK
3	1	-912 VITON 75A	O-RING -912 VITON 75A
2	1	1386	HOUSING SO16-SS
1	4	CMS-TO-1425-HT	TAB QUICK DISCONNECT MALE .25 WIDE
ITEM	QTY	PART NUMBER	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION *PAVE-Mate® 1 Connectors*
SO16-SS-200-4-14-T-T

PART NUMBER
2091

