


**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MW .01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.

3	6@73.36	KXG16	CABLE T/C TYPE K 16 AWG GLASS B
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1625	HOUSING PT16-SS
<b>ITEM</b>	<b>QTY</b>	<b>PART#</b>	<b>DESCRIPTION</b>


 2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

DESCRIPTION PAVE-Seal® Cable Harnesses  
**PT16-SS-150-6P-KXG16-36-36**

PART NUMBER **2161** PROJECTION 

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/- .5  
 .X DECIMAL +/- .1 .XX DECIMAL +/- .02 .XXX DECIMAL +/- .005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS