



- NOTES:
1. HE LEAK TEST @1 ATM. 10^{-6} CC/S.
 2. HYPOT 630 VDC 500 MW 0.01 SEC MINIMUM, WIRE TO WIRE & HOUSING.
 3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
 4. PERCENTAGE OF PARTS TESTED WILL BE 100% (MAY BE

A LESSER PERCENTAGE FOR LARGE PRODUCTION QUANTITIES, UNLESS OTHERWISE NOTED OR REQUIRED).

6	30@4m	RG316	B83284 OR EQUAL BELDEN 83284
5	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
4	1	-231 VITON	O-RING -231 VITON 75
3	A/R	PAVE-Seal 150	EPOXY BLACK
2	1	0102	NUT VS32-SS
1	1	0101	HOUSING VS32-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Seal® Cable Harnesses
 VS32-SS-150-30-RG316-2-2m

PART NUMBER
2482

REVISION LEVEL -
 PROJECTION