



NOTES:

1. LEAK TEST: 225 PSI, NO BUBBLES 30 SECONDS MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. CONTINUITY TEST PINS TO WIRES: <.5 OHM
4. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
5. ALL PARTS MUST PASS ALL TESTS.
6. NO VOIDS ARE ACCEPTABLE ON O-RING SEALING SURFACES, VOIDS SMALLER THAN ϕ .035 ARE ACCEPTABLE ON ALL OTHER SURFACES.
7. REF-OPERATING TEMPERATURE -40°C TO 150°C.
8. ITEMS 3 & 4 ARE INCLUDED, BUT NOT SHOWN.

13	A/R	PAVE-Seal 150	EPOXY BLACK
12	1	E26 PURPLE	WIRE 26E MIL-W-16878/4 7/#34
11	1	E26 BLUE	WIRE 26E MIL-W-16878/4 7/#34
10	1	E26 WHITE	WIRE 26E MIL-W-16878/4 7/#34
9	1	E26 ORANGE	WIRE 26E MIL-W-16878/4 7/#34
8	1	E26 BROWN 7 STR	WIRE 26E MIL-W-16878/4 7/#34
7	1	E26 RED	WIRE 26E MIL-W-16878/4 7/#34
6	1	E26 GREEN	WIRE 26E MIL-W-16878/4 7/#34
5	1	E26 BLACK 7STRD	WIRE 26E MIL-W-16878/4 7/#34
4	1	M85049/38-13N	S/R FOR D38999/26FC8S
3	1	26FC8S	PLUG 8#20 SOC 999 SERIES III
2	1	20FC8P	RCPT 8#20 PIN 999 SERIES III
1	1	3238	HOUSING PT8-SS
ITEM	QTY	PART NUMBER	DESCRIPTION

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
PT8-SS-150-8-TE26-99920P-36

PART NUMBER
3168

REVISION LEVEL
B

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS