



NOTES:

1. LEAK TEST: 200 PSI, NO BUBBLES 2 MINUTES MINIMUM.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & VARIABLE.
6. COSMETIC SURFACE VOIDS SMALLER THAN $\phi 0.035$ [.89] ARE ACCEPTABLE.
7. REF-OPERATING TEMPERATURE -20 °C TO 125 °C.
8. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.
9. DIMENSIONS ARE INCHES [millimeters].
10. ITEMS 5 & 7 WILL BE TWISTED PAIRS & ITEMS 6 & 7 WILL BE TWISTED PAIRS @ APPROXIMATELY 1-3 TWISTS PER INCH BOTH SIDES.

ITEM	QTY	PART NUMBER	DESCRIPTION
9	1	0185	NUT VS26-SS
8	1	-226 VITON	O-RING -226 VITON 75
7	8	E22 19 WHITE	WIRE 22E MIL-W-16878/4 .010 19/#34
6	4	E22 19 ORG	WIRE 22E MIL-W-16878/4 .010 19/#34
5	4	E22 19 GREEN	WIRE 22E MIL-W-16878/4 .010 19/#34
4	4	E22 19 BLACK	WIRE 22E MIL-W-16878/4 .010 19/#34
3	4	E22 19 RED	WIRE 22E MIL-W-16878/4 .010 19/#34
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	1531	HOUSING VS26-SS

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE ± 0.5
 X.X DECIMAL ± 0.1 X.XX DECIMAL ± 0.02 X.XXX DECIMAL ± 0.005
 ANGLES ± 1 DEGREE SURFACE FINISH 128 microinch RMS

PAVE technology co.
 2751 Thunderhawk Court
 Dayton, OH 45414-3445
 U.S.A.
 tel (937) 890-1100
 fax (937) 8905165
 www.pavetechnologyco.com

DESCRIPTION
 VS26-SS-150-24-TE22-60-60

PART NUMBER
4494

MATERIAL NOTED

REVISION LEVEL -

PROJECTION