



**NOTES:**

1. LEAK TEST: 80 PSI, NO BUBBLES 3 MINUTES MINIMUM. A GREEN PAINT DOT INDICATES THE PART HAS PASSED THE TEST.
2. HYPOT 630 VDC 500 MEGOHMS MINIMUM 0.01 SECOND MINIMUM WIRE TO WIRE AND HOUSING.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ALL PARTS MUST PASS ALL TESTS.
5. WIRE POSITIONING IS APPROXIMATE & COLOR POSITIONS ARE VARIABLE.
6. COSMETIC SURFACE VOIDS LARGER THAN  $\phi .035$  [0.89] ARE NOT ACCEPTABLE.
7. REF-OPERATING TEMPERATURE RANGE  $-75^{\circ}\text{C}$  TO  $200^{\circ}\text{C}$ .
8. DIMENSIONS ARE INCHES [millimeters].
9. PAVE-SEAL CAN BE A BI-DIRECTIONAL HERMETIC SEAL FOR VACUUM AND MOST PRESSURES. FOR PRESSURES ABOVE 150 PSI (10 BAR), CHECK WITH SALES ENGINEERING.

6	1	EE22 UL1180 BLU	WIRE 22EE UL1180 7/#30 BLUE
5	1	EE22 UL1180 WHT	WIRE 22EE UL1180 MARKED 7/#30
4	1	EE22 UL1180 RED	WIRE 22EE UL1180 MARKED 7/#30
3	1	EE22 UL1180 BLK	WIRE 22EE UL1180 MARKED 7/#30
2	A/R	PAVE-Seal 200	EPOXY BLACK
1	1	0346	HOUSING PT-8 SS
<b>ITEM</b>	<b>QTY</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>

**PAVE technology co.**

2751 Thunderhawk Court  
Dayton, OH 45414-3445  
U.S.A.  
tel (937) 890-1100  
fax (937) 8905165  
www.pavetechnologyco.com

DESCRIPTION  
PT8-SS-200-4-TEE22-48-6

PART NUMBER  
**5073**

MATERIAL NOTED

REVISION LEVEL -

PROJECTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES.  
ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE  $\pm 0.5$   
X.X DECIMAL  $\pm 0.1$  X.XX DECIMAL  $\pm 0.02$  X.XXX DECIMAL  $\pm 0.005$   
ANGLES  $\pm 1$  DEGREE. SURFACE FINISH 128 microinch RMS