



NOTES:

1. HE LEAK TEST @1 ATM. 10^{-7} CC/S.
2. CHECK OPTICAL CONTINUITY UNDER MICROSCOPE.
3. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
4. ITEM 3 CUSTOMER SUPPLIED.
5. HANDLE ITEM 3 CAREFULLY-2" DIA MIN COIL GLASS FIBER BREAKS WHEN BENT SHARPLY.

7	1	0894	NUT VS8-SS
6	A/R	SUPER O-LUBE	LUBRICANT O-RING SILICONE BASED
5	A/R	-112 VITON	O-RING -112 VITON 75A
4	6x1	A-STT-30	TUBING .012"ID TEFLON SPAGHETTI
3	3X13"	FGP100140170Z	FIBER OPTICAL BROWN 100um/140um/170um
2	A/R	PAVE-Seal 150	EPOXY BLACK
1	1	0892	HOUSING VS8-SS
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS



DESCRIPTION PAVE-Opti Seal/Fromans.shx; Cable Harnesses

VS8-SS-80-3-FO-6-6

PART NUMBER

2271

PROJECTION

