



NOTES:

1. HIPOT 2500 VAC: 5 mA MAX LEAKAGE FROM CENTER CONDUCTOR TO SHELL.

| 4 | 1 | TIN COPPER #20 | WIRE BUS #20 TINNED |
|------|------|----------------|---|
| 3 | 1 | AMPH# 10400 | PLUG MHVST JCK BHD REC |
| 2 | 2.5g | TRA-BOND F202 | EPOXY CLEAR |
| 1 | 1 | U-SWTT-20 | TUBING TEFLON 0.034 SEMI FLEXIBLE 0.016 |
| ITEM | QTY | PART NUMBER | DESCRIPTION |

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE #0.5
 XX DECIMAL ±0.1 XXX DECIMAL ±0.02 XXXX DECIMAL ±0.005
 ANGLES ±1 DEGREE SURFACE FINISH 128 microinch RMS

| | | |
|----------------------------|---|----------------|
| | 2751 Thundehawk Court Dayton, OH 45414-3445 U.S.A. tel (937) 890-1100 fax (937) 8905165 www.pave-technology.co.com | |
| | DESCRIPTION VSBNC-SS-200-1-CRTFE18-BNC-13 | |
| PART NUMBER 2628 | REVISION LEVEL A | PROJECTION |