



NOTES:

1. HE LEAK TEST @1 ATM. <math>10^{-6}</math> CC/S ON A SAMPLE OF EACH LOT, USING -028 VITON O-RING, LUBRICATED WITH SUPER O-LUBE.
2. ALL TESTS ARE PERFORMED AT ROOM TEMPERATURE.
3. REF - OPERATING TEMPERTURE RANGE: -40 TO 75°C.

6	A/R	PAVE-Seal 150	EPOXY BLACK
5	1	2483	AVESTOR P0012650
4	1	PC10 RD	WIRE PVC #10 AWG 7X15/30 BARE COPPER
3	1	PC10 BLACK	WIRE PVC #10 AWG 7X15/30 BARE COPPER
2	1	2518	CABLE RIBBON 16 #28 SOLID (3M #3709/16)
1	1	2517	CABLE RIBBON 20 #28 SOLID (3M #3709/20)
ITEM	QTY	PART#	DESCRIPTION

ALL DIMENSIONS AND TOLERANCES APPLY TO FINISHED PART IN INCHES  
 ALLOWABLE TOLERANCES UNLESS SPECIFIED OTHERWISE: NONE +/-0.5  
 .X DECIMAL +/- 0.1 .XX DECIMAL +/- 0.02 .XXX DECIMAL +/-0.005  
 ANGLES +/- 1 DEG SURFACE FINISH 128 microinch RMS

2751 Thunderhawk Court  
 Dayton, Ohio 45414-3445  
 U.S.A.  
 (937)890-1100  
 fax (937)890-5165  
 www.pavetechnologyco.com

**PAVE technology co.**

DESCRIPTION PAVE-Seal Cable Harnesses  
 SP24-E-150-2/1/1-PC10/20RIB/16RIB-\*

PART NUMBER 3187

REVISION LEVEL A

PROJECTION